



6×Fi (25) SK11J09

構成 6×Fi[1+6+ (6) +12]

用途 一般クレーン用、ロープウェイ用、エレベータ用

規格

ロープ径 mm	上層素線径 mm		断面積 mm <sup>2</sup>		破断力								(参考) 単位質量 kg/m
					裸・めっき						裸		
					E 種		A 種		B 種		T 種		
					kN	(参考) tf	kN	(参考) tf	kN	(参考) tf	kN	(参考) tf	
6	0.39	(0.39)	15.1	( 14.2)	16.1	1.64	19.6	1.99	20.9	2.13	22.0	2.24	0.139
6.3	0.41	(0.41)	16.6	( 15.7)	17.8	1.81	21.6	2.20	23.0	2.34	24.2	2.46	0.153
8	0.52	(0.51)	26.8	( 25.2)	28.6	2.91	34.9	3.55	37.2	3.79	39.1	3.98	0.247
9	0.59	(0.58)	33.9	( 31.9)	36.2	3.69	44.1	4.49	47.0	4.79	49.5	5.04	0.312
10	0.65	(0.64)	41.9	( 39.4)	44.7	4.55	54.5	5.55	58.1	5.92	61.1	6.23	0.386
11.2	0.73	(0.72)	52.6	( 49.5)	56.1	5.72	68.3	6.96	72.8	7.42	76.6	7.81	0.484
12	0.79	(0.77)	60.4	( 56.8)	64.4	6.56	78.5	8.00	83.7	8.53	88.0	8.97	0.556
12.5	0.82	(0.81)	65.5	( 61.6)	69.9	7.12	85.1	8.67	90.7	9.24	95.4	9.72	0.603
14	0.92	(0.90)	82.1	( 77.3)	87.7	8.94	107	10.9	114	11.6	120	12.2	0.756
16	1.05	(1.03)	107	(101 )	115	11.7	139	14.1	149	15.1	156	15.9	0.988
18	1.17	(1.15)	136	(128 )	145	14.7	176	17.9	188	19.1	198	20.1	1.25
20	1.30	(1.28)	168	(158 )	179	18.2	218	22.2	232	23.6	244	24.8	1.54
22.4	1.45	(1.43)	210	(198 )	224	22.8	273	27.8	291	29.6	306	31.2	1.94
25	1.63	(1.60)	262	(247 )	280	28.5	340	34.6	363	37.0	382	38.9	2.41
28	1.83	—	329	—	—	—	427	43.5	455	46.3	479	48.8	3.02
30	1.94	—	377	—	—	—	490	49.9	523	53.3	550	56.0	3.47
31.5	2.06	—	416	—	—	—	540	55.0	576	58.7	606	61.7	3.83
33.5	2.17	—	470	—	—	—	611	62.3	652	66.4	685	69.8	4.33
35.5	2.30	—	528	—	—	—	686	69.9	732	74.6	770	78.5	4.86
37.5	2.44	—	589	—	—	—	766	78.1	816	83.2	859	87.5	5.43
40	2.58	—	671	—	—	—	871	88.8	929	94.7	977	99.6	6.17

※ エレベータ用は ( ) の数値になっております。