



IWRC 6×Fi (25) SK11J10

構 成 7×7+6×Fi[1+6+ (6) +12]

用 途 一般クレーン用

規 格

ロープ径 mm	上層素線径 mm	断面積 mm ²	破断力				(参考) 単位質量 kg/m
			裸・めっき		裸		
			B 種		T 種		
			kN	(参考) tf	kN	(参考) tf	
10	0.65	49.4	66.2	6.75	69.5	7.08	0.430
11.2	0.73	61.9	83.0	8.46	87.2	8.89	0.539
12.5	0.82	77.1	103	10.5	109	11.1	0.672
14	0.92	96.7	130	13.2	136	13.8	0.843
16	1.05	126	169	17.2	178	18.1	1.10
18	1.17	160	214	21.8	225	22.9	1.39
20	1.30	197	265	27.0	278	28.3	1.72
22.4	1.45	248	332	33.8	349	35.5	2.16
25	1.63	309	414	42.2	435	44.3	2.69
28	1.83	387	519	52.9	545	55.5	3.37
30	1.94	444	596	60.7	626	63.8	3.87
31.5	2.06	490	657	66.9	690	70.3	4.27
33.5	2.17	554	743	75.7	780	79.5	4.83
35.5	2.30	622	834	85.0	876	89.3	5.42
37.5	2.44	694	931	94.9	978	99.7	6.05
40	2.58	790	1,060	108	1,110	113	6.88