



6×Fi (29) SK11J11

構成 6×Fi[1+7+ (7) +14]

用途 一般クレーン用、索道用

規格

ロープ径 mm	上層素線径 mm	断面積 mm ²	破断力				(参考) 単位質量 kg/m
			裸・めっき		裸		
			B 種		T 種		
			kN	(参考) tf	kN	(参考) tf	
8	0.46	27.2	37.9	3.86	39.9	4.06	0.253
9	0.52	34.5	48.0	4.89	50.4	5.13	0.321
10	0.57	42.6	59.2	6.03	62.3	6.35	0.396
11.2	0.64	53.4	74.3	7.57	78.1	7.96	0.496
12.5	0.72	66.5	92.5	9.43	97.3	9.92	0.618
14	0.81	83.4	116	11.8	122	12.4	0.776
16	0.92	109	152	15.4	159	16.2	1.01
18	1.03	138	192	19.5	202	20.5	1.28
20	1.14	170	237	24.1	249	25.3	1.58
22.4	1.28	213	297	30.2	312	31.8	1.99
25	1.43	266	370	37.7	389	39.6	2.47
28	1.60	334	464	47.3	488	49.7	3.10
30	1.70	383	533	54.3	560	57.1	3.56
31.5	1.80	422	588	59.9	618	63.0	3.93
33.5	1.91	478	665	67.8	699	71.2	4.44
35.5	2.03	536	746	76.0	785	80.0	4.99
37.5	2.14	598	833	84.9	876	89.3	5.57
40	2.27	681	948	96.6	996	101	6.33
42.5	2.40	769	1,070	109	1,120	114	7.15
45	2.58	862	1,200	122	1,260	128	8.01
47.5	2.70	960	1,340	136	1,400	142	8.93
50	2.86	1,060	1,480	150	1,560	159	9.90
53	3.03	1,200	1,660	169	1,750	178	11.1
56	3.20	1,330	1,860	189	1,950	198	12.4
60	3.45	1,530	2,130	217	2,240	228	14.2