



6×WS (26) SK11J13

構 成 6×WS[1+5+ (5+5) +10]

用 途 一般クレーン用、索道用

規 格

ロープ径 mm	上層素線径 mm	断面積 mm ²	破断力				(参考) 単位質量 kg/m
			裸・めっき		裸		
			B 種		T 種		
			kN	(参考) tf	kN	(参考) tf	
8	0.60	26.8	37.2	3.79	39.1	3.98	0.247
9	0.68	33.9	47.0	4.79	49.5	5.04	0.312
10	0.75	41.9	58.1	5.92	61.1	6.23	0.386
11.2	0.84	52.6	72.8	7.42	76.6	7.81	0.484
12	0.90	60.4	83.6	8.52	88.0	8.97	0.556
12.5	0.95	65.5	90.7	9.24	95.4	9.72	0.603
14	1.06	82.1	114	11.6	120	12.2	0.756
16	1.20	107	149	15.1	156	15.9	0.988
18	1.35	136	188	19.1	198	20.1	1.25
20	1.50	168	232	23.6	244	24.8	1.54
22.4	1.68	210	291	29.6	306	31.2	1.94
25	1.88	262	363	37.0	382	38.9	2.41
28	2.11	329	455	46.3	479	48.8	3.02
30	2.24	377	523	53.3	550	56.0	3.47
31.5	2.37	416	576	58.7	606	61.7	3.83
33.5	2.51	470	652	66.4	685	69.8	4.33
35.5	2.66	528	732	74.6	770	78.5	4.86
37.5	2.82	589	816	83.2	859	87.5	5.43
40	3.00	671	929	94.7	977	99.6	6.17