



# モノロープEP

3×F(40) SK11M01

構成 3×F[a+8+ (8+8) +16]

用途 タワークレーン巻上索

東京製綱規格

ロープ径 mm	上層素線径 mm	断面積 mm <sup>2</sup>	破断力				(参考) 単位質量 kg/m
			普通より				
			裸・めっき		裸		
			B 種		T 種		
			kN	(参考) tf	kN	(参考) tf	
10	0.80	47.0	78.9	8.04	85.5	8.71	0.436
11.2	0.89	58.9	99.0	10.0	107	10.9	0.547
12	0.96	67.6	114	11.6	123	12.5	0.628
12.5	1.00	73.4	123	12.5	134	13.6	0.681
14	1.12	92.1	155	15.8	168	17.1	0.855
16	1.28	120	202	20.5	219	22.3	1.12
18	1.43	152	256	26.1	277	28.2	1.41
20	1.58	188	316	32.2	342	34.8	1.74
22	1.75	227	382	38.9	414	42.2	2.11
22.4	1.78	236	396	40.3	429	43.7	2.19
24	1.91	271	455	46.3	493	50.2	2.51
25	2.00	294	493	50.2	534	54.4	2.73
26	2.06	318	533	54.3	578	58.9	2.95
28	2.24	368	619	63.1	670	68.3	3.42
30	2.37	423	710	72.3	770	78.5	3.92
31.5	2.51	466	783	79.8	849	86.5	4.33
32	2.55	481	808	82.3	876	89.3	4.47
33.5	2.66	527	886	90.3	960	97.8	4.89
34	2.70	543	912	92.9	989	100	5.04
35.5	2.82	592	994	101	1,080	110	5.50
36	2.86	609	1,020	104	1,110	113	5.65
37.5	3.00	661	1,110	113	1,200	122	6.13
38	3.03	678	1,140	116	1,230	125	6.30
40	3.16	752	1,260	128	—	—	6.98
42.5	3.35	848	1,430	145	—	—	7.88