



モノロープA

4×F (30) SK11M02

構 成 4×F (a+15+15)

用 途 タワークレーン巻上索

東京製綱規格

ローブ径 mm	上層素線径 mm	断面積 mm ²	破断力				(参考) 単位質量 kg/m
			普通より				
			裸・めっき		裸		
			B 種		T 種		
			kN	(参考) tf	kN	(参考) tf	
8	0.57	24.1	36.0	3.67	39.0	3.97	0.221
9	0.65	30.4	45.5	4.63	49.3	5.02	0.279
10	0.72	37.6	56.2	5.73	60.9	6.21	0.345
11.2	0.81	47.2	70.5	7.18	76.4	7.79	0.432
12	0.87	54.1	81.0	8.25	87.7	8.94	0.496
12.5	0.90	58.7	87.9	8.96	95.2	9.70	0.539
14	1.02	73.7	110	11.2	119	12.1	0.676
16	1.15	96.2	144	14.6	156	15.9	0.882
18	1.30	122	182	18.5	197	20.0	1.12
20	1.43	150	225	22.9	244	24.8	1.38
22	1.58	182	272	27.7	295	30.0	1.67
22.4	1.60	189	282	28.7	306	31.2	1.73
24	1.73	217	324	33.0	351	35.7	1.99
25	1.80	235	351	35.7	381	38.8	2.15
26	1.86	254	380	38.7	412	42.0	2.33
28	2.03	295	441	44.9	478	48.7	2.70
30	2.14	338	506	51.5	548	55.8	3.10
31.5	2.27	373	558	56.9	604	61.5	3.42
32	2.30	385	576	58.7	624	63.6	3.53
33.5	2.40	422	631	64.3	684	69.7	3.87
34	2.44	435	650	66.2	704	71.7	3.98
35.5	2.55	474	709	72.2	768	78.3	4.34
36	2.58	487	729	74.3	789	80.4	4.47
37.5	2.70	529	791	80.6	857	87.3	4.85
38	2.74	543	812	82.8	880	89.7	4.98
40	2.86	601	900	91.7	975	99.4	5.52
42.5	3.03	679	1,020	104	1,100	112	6.23
44	3.16	728	1,090	111	—	—	6.67
45	3.25	761	1,140	116	—	—	6.98