



モノロープSP

4×F (40) SK11M03

構成 4×F[a+8+ (8+8) +16]

用途 タワークレーン巻上索、デリック巻上索 (高揚程)

東京製綱規格

ロープ径 mm	上層索線径 mm	断面積 mm ²	破断力				(参考) 単位質量 kg/m
			普通より				
			裸・めっき		裸		
			B 種		T 種		
			kN	(参考) tf	kN	(参考) tf	
8	0.53	29.0	43.0	4.38	46.5	4.74	0.258
9	0.61	36.7	54.4	5.54	58.9	6.00	0.327
10	0.67	45.3	67.1	6.84	72.7	7.41	0.403
11.2	0.75	56.8	84.2	8.58	91.2	9.29	0.506
12	0.81	65.2	96.7	9.86	105	10.7	0.581
12.5	0.84	70.8	105	10.7	114	11.6	0.630
14	0.95	88.7	132	13.4	143	14.5	0.790
16	1.08	116	172	17.5	186	18.9	1.03
18	1.20	147	218	22.2	236	24.0	1.31
20	1.33	181	269	27.4	291	29.6	1.61
22	1.47	219	325	33.1	352	35.8	1.95
22.4	1.50	227	337	34.3	365	37.2	2.02
24	1.60	261	387	39.4	419	42.7	2.32
25	1.68	283	420	42.8	455	46.3	2.52
26	1.73	306	454	46.2	492	50.1	2.73
28	1.88	355	526	53.6	570	58.1	3.16
30	2.00	408	604	61.5	655	66.7	3.63
31.5	2.11	449	666	67.9	722	73.6	4.00
32	2.14	464	687	70.0	745	75.9	4.13
33.5	2.24	508	753	76.7	816	83.2	4.52
34	2.27	523	776	79.1	841	85.7	4.66
35.5	2.37	571	846	86.2	917	93.5	5.08
36	2.40	587	870	88.7	943	96.1	5.23
37.5	2.51	637	944	96.2	1,020	104	5.67
38	2.55	654	969	98.8	1,050	107	5.82
40	2.66	724	1,070	109	1,160	118	6.45
42.5	2.82	818	1,210	123	1,310	133	7.28