



## 規格

使用荷重 KN	ロープ径 (呼び) mm	捻 径	全 長		接 合 ボルト	デッドアイ 重量 kg	(参考) 重量 kg
			MIN	MAX			
20.6	14	M24	488	700	M22	0.95	5.97
25.5	16	M27	538	770	M24	1.6	8.58
32.4	18	M30	590	836	M27	1.9	11.6
50.0	20 ~ 22	M33	638	908	M27	2.7	14.8
57.9	24	M39	688	968	M30	3.65	19.4
67.7	25	M42	720	1,004	M33	4.6	23.9
90.2	28 ~ 30	M48	770	1,074	M39	6.3	30.2
103.0	32	M48	810	1,124	M39	7.2	36.2
112.8	34	M52	850	1,176	M42	8.6	43.2
127.5	36	M56	900	1,238	M45	9.9	51.1
142.2	38	M60	938	1,284	M48	12.5	59.9
161.8	40	M64	988	1,344	M52	15.7	70.7
181.4	42	M68	1,068	1,444	M56	17.8	81.9
206.0	45	M68	1,100	1,482	M60	20.7	105
226.0	48	M76	1,140	1,536	M64	24.2	117
250.1	50	M76	1,160	1,556	M64	24.2	124